

R&D Towards a Muon Collider

H. Guler (undergraduate student), C. Lu, K.T. McDonald,

E.J. Prebys, S.E. Vahsen (graduate student)

Princeton U.

May 26, 1998

Muon Collider main page:

`http://www.cap.bnl.gov/mumu/mu_home_page.html`

Princeton muon collider page:

`http://www.hep.princeton.edu/~mcdonald/mumu`

Options for Future Colliders

- Hadron collider (LHC, SSC): $\approx$ \$100k/m [superconducting magnets].

  $\approx$ 2 km per TeV of CM energy.

  Ex: LHC has 14-TeV CM energy, 27 km ring, $\approx$ \$3B.

- Linear e^+e^- collider (SLAC, NLC(?)): $\approx$ \$200k/m [rf].

  $\approx$ 20 km per TeV of CM energy;

  But a lepton colliders needs only $\approx 1/5$ the CM energy to have equivalent physics reach to a hadron collider.

  Ex: NLC has 3-TeV CM energy, 30 km long, $\approx$ \$6B (?).

- Muon collider: $\approx$ \$1B for source/cooler + \$100k/m for rings

  Well-defined leptonic initial state.

  $m_\mu/m_e \approx 200 \Rightarrow$ Little beam radiation.

  $\Rightarrow$ Can use storage rings.

  $\Rightarrow$ Smaller footprint.

  Technology: closer to hadron colliders.

  $\approx$ 6 km of ring per TeV of CM energy.

  Ex: 3-TeV muon collider $\approx$ \$3B (?).

The Case for a Muon Collider

- More affordable than an e^+e^- collider at the TeV (LHC) scale.
- More affordable than either a hadron or an e^+e^-collider for (effective) energies beyond the LHC.
- Initial machine could produce light Higgs via s-channel.

  Higgs coupling to μ is $(m_\mu/m_e)^2 \approx 40,000\times$ that to e.

  Beam energy resolution at a muon collider $< 10^{-5}$,

  $\Rightarrow$ Measure Higgs width.

  Add rings to 3 TeV later.
- Neutrino beams from μ decay about 10^4 hotter than present.

Ingredients of a Muon Collider

An accelerator complex in which

- Muons (both μ^+ and μ^-) are collected from pion decay following a pN interaction.
- The muon phase volume is reduced by ionization cooling.
- The cooled muons are accelerated and then stored in a ring.
- $\mu^+\mu^-$ collisions are observed over the useful muon life of ≈ 1000 turns at any energy.

Muons decay: $\mu \to e\nu \qquad \Rightarrow$

- Must cool muons quickly (stochastic cooling won't do).
- Detector backgrounds at LHC level.
- Personnel background from ν interactions.

Footprints



Muon collider:

- Significant base cost ($\approx$ \$1B) at any energy,

  plus 'modest' cost ($\approx$ \$100k/m) for storage rings.

- Up to 4 TeV on existing sites at cost below LHC.

- Technology path to $\approx$ 100 TeV before limited by radiation losses.

Technical Challenges

- 16-GeV proton driver, 15 Hz, 4-MW beam power, 1-ns bunch length.
- **Targetry and Capture**
- **Muon Cooling**
- Storage rings have beautiful, highly corrected solutions due to heroic work of Al Garren, Carol Johnstone and Dan Trbojevič.

Overview of Targetry for a Muon Collider



- 1.2×10^{14} $\mu^{\pm}$/s via π-decay from 4-MW proton beam.
- Cooling jacket around stationary target would absorb too many pions.
- Liquid metal jet target: Ga, Hg, or solder (Bi/In/Pb/Sn).
- 20-T capture solenoid followed by 1.5-T π-decay channel with phase-rotation via rf (to compress energy of the muon bunch).