



Thermal, Mechanical and Fluid Flow Challenges of the FRIB Primary Beam Dump

Mikhail Avilov

Facility for Rare Isotope Beams

Michigan State University

MICHIGAN STATE
UNIVERSITY



U.S. DEPARTMENT OF
ENERGY

Office of
Science


Outline

- FRIB primary Beam Dump Concept and Technical Requirements
- Overview of Challenges for the Beam Dump
- Mechanical Challenges
- Thermal and Thermo-mechanical Challenges
- Fluid Challenges
- Chemical Challenges
- Radiation Challenges
- Summary

Facility for Rare Isotope Beams


- World-leading heavy ion accelerator facility for rare isotope science

- Nuclear Structure
- Nuclear Astrophysics
- Fundamental Interactions
- Isotopes for Societal Needs



Scope and Technical Requirements

- Rare isotope production targets and beam dump compatible with beam power of 400 kW at 200 MeV/u for ^{238}U (>200 MeV/u for lighter ions)



Slide 4

PF1



Pellemoine, Frederique, 5/5/2014

Primary Beam Dump

Water-filled Rotating Drum Concept

- Beam Dump requirements
 - High power capability up to 325 kW
 - 1 year (5500 h) lifetime desirable
 - Remote replacement and maintenance
- Water-filled rotating drum concept chosen for FRIB baseline
 - Using water to stop the primary beam and absorb beam power
- Design parameters
 - Ti-alloy shell thickness 0.5 mm to minimize power deposition in shell
 - 400 rpm and 70 cm diameter to limit maximum temperature and amplitude of temperature changes
 - 60 gpm water flow to provide cooling and gas bubble removal

Beam Dump schematic layout



Beam Dump Challenges Overview

Challenge

Mechanical

vibration

mechanical resonances

pressure-induced stress

Thermal and thermo-mechanical

thermal stress

fatigue

stress wave

thermal creep

Fluid

bubble formation: nucleate boiling

bubble formation: cavitation

wall heat transfer

Challenge

Chemical

corrosion

radiolysis

Radiation

radiation damage of materials

sputtering



radiation creep

- Some effects may be enhanced by the presence of the other
- Up to now no facility exists to study the combination of all these effects => perform studies that combine some challenges using existing facilities

Mechanical Challenges

Vibration, Mechanical Resonances, Internal Pressure

- Stress induced by internal pressure
 - Studied numerically
 - The optimization of the BD shell geometry performed in order to better withstand the increased pressure level due to BD rotation
 - Safety factor of 5 calculated
 - Verified by the mockup tests





- Mechanical resonances
 - Studied numerically, the operation rotating frequency range found to be far below the first resonance peak.
 - Safety factor of > 90 calculated
 - Mechanical test of mockup did not reveal major issues

Mechanical Challenges

Mockup Tests to Confirm Mechanical Design


- Beam dump mock-up tests at ORNL performed to evaluate mechanical and flow design
 - Parametric study over flow parameter range
 - » Rotation speed, flow rates, pressures, angle
 - » Evaluation of pressure drops
- Additional prototypic operation verified
 - Mechanical balance
 - Fill and drain tests
 - Reliability




Thermal and Thermo-mechanical Challenges

Thermal Stress in the BD Shell

- High power beam induces high level of thermal stress in the BD shell
 - Thermal and mechanical conditions are numerically simulated for different primary beams and different rigidities
- In the most severe case with U beam:
 - Temperature: 350 ± 150 °C (limited by 500 °C to prevent corrosion)
 - Thermal stress: 250 ± 150 MPa
- Far below the stress limit for Ti-6Al-4V alloy
 - 800 – 900 MPa



Calculated temperature profile in the Beam Dump shell




Calculated stress profile in the Beam Dump shell

Thermal and Thermo-mechanical Challenges

Fatigue and Stress Wave

■ Fatigue


- BD rotation -> cyclic thermal load from the beam -> possible fatigue issues
- BD must survive $1.e8$ cycles
- Adding 1% of B to Ti-6Al-4V alloy could improve significantly fatigue properties of the shell, increasing the safety factor for all primary beams and rigidities
- **Validation tests required** as simulation gives large dispersion in results with respect to the input parameters
- Corrosion and radiation damage may affect significantly the fatigue life



Fatigue safety factor comparison for Ti-6Al-4V and Ti-6Al-4V-1B alloys

■ Stress wave

- Is a result of the beam impact to the rotating surface. Contributes to the total stress in the BD shell
- Simulation performed revealed stress wave contribution $\sim 10\%$ of the total stress



Stress wave propagation in the BD shell



Fluid Challenges

Bubble Formation: Boiling and Cavitation


- Boiling – bubble formation due to high power deposition in water and in the shell
- Cavitation – bubble formation due to rapid change of pressure
- Bubble formation -> bubble collapse -> shockwave -> possible BD shell damage
 - Study of bubble formation on the shell is in progress
 - Cavitation study – simulation and test
 - Simulation showed no critical pressure changes
 - BD mockup flow test did not reveal cavitation



A movie from the test



Flow test with transparent (acrylic) beam dump




Pressure drop simulation




Fluid Challenges

Wall Heat Transfer [1]

- Good heat transfer is essential for heat removal from the shell => highly turbulent water flow required. CFD simulation – wall heat transfer improved by introducing the turbine and insert



- Nucleate boiling** allows to obtain an order of magnitude larger heat transfer
 - Critical heat flux is one of the most essential parameters: exceeding it will result in transition to the film boiling -> failure




Boiling diagram

Fluid Challenges

Wall Heat Transfer [2]


Study:

- Collaboration with Fluid Mechanic Institute of Toulouse established (expertise in transitory boiling problem in nuclear power plant)
- Simulation of the BD fluid and thermal conditions with NEPTUNE code
- **Q:** How can fast rotation help in bubble removal from the BD shell thus improving the heat transfer?




Tests:

- Tests intended to evaluate the heat flux transfer through the shell
- Electron beam will be used to heat the mockup
- Other issues (like fatigue or bubble formation) are possible to study




Chemical challenges

Corrosion, radiolysis



Beam spot on the BD shell



■ Corrosion

- Ti-6Al-4V temperature must be limited by 500 °C to avoid strong corrosion in water
- Reduced power densities for few ion beams at few rigidities could be used
- Nanoscale corrosion studies during SHI irradiation at Sandia Lab

■ Radiolysis

- Liberates hydrogen and oxygen gas and produces hydrogen peroxide that may impact the BD shell
- Gas production estimates did not reveal substantial quantities of H, O and HO₂
- Water circulation helps to prevent the gas accumulation
- Adding H₂ (3 ppm) mitigates radiolysis

Radiation challenges

Radiation damage of Ti alloy and Sputtering

- Irradiation test with Ti-6Al-4V and Ti-6Al-4V-1B alloys
 - Irradiation tests were performed at IRRSUD (GANIL, Caen, France)
 - No evidence of Phase transformation and ion track was shown at 3 irradiations (^{82}Kr at 25 and 45 MeV and ^{131}Xe at 92 MeV)
 - More tests ongoing at IRRSUD
 - Samples of Ti-6Al-4V-1B were irradiated at NSCL with ^{40}Ca beam at 50 MeV/u


Talk of F. Pellemoine, this workshop

CiMap

Energy loss vs. specific energy for nuclear (blue) and electronic (red) sputtering

- Sputtering

- A process of surface erosion due to bombardment by the ions
- Sputtering is stronger in insulators (TiO_2)
- Sputtering evaluation for Ti and TiO_2 (M. Toulemonde, GANIL): U beam at 160 MeV/u
- Thickness of sputtered layers were estimated to be 0.2 nm/year for Ti, 1 micron/year for TiO_2 – should not be an issue



Conclusions

- Water-filled rotating drum concept of the beam dump is chosen for the FRIB baseline
- No show-stoppers but challenges exist and are being addressed
- Some effects may be enhanced by the presence of the other (e.g. – corrosion in presence of radiation, stress limit in the presence of radiation)
 - Up to now no facility exists to study an impact from all the effects combined
 - All challenges were studied case-by-case experimentally and in simulation
- Solutions found for most issues that could negatively impact on the BD operation
- Some studies (in particular, BD fluid flow/boiling/shell heat transfer) ongoing

Acknowledgements

FRIB-MSU:

Frederique Pellemoine
Wolfgang Mittig
Mike Schein
Tiffany Fourmeau
Reginald Ronningen

ORNL:

Adam Aaron
Adam Carroll
Van Graves
Tom Burgess

MSU Department of Chemical Engineering and Material Science:

Carl Boehlert
Aida Amroussia

Institute of Fluid Mechanics (Toulouse, France):

Catherine Colin
Wladimir Bergez

GANIL:

Marcel Toulemonde

Thanks for your attention!

Backup slides

Thermal creep evaluation


Creep strain at failure: 0.32

Corresponds to >1000 h of operation.


Creep strain after 2 weeks = 0.1

Creep strain after 5500 hours = 1.6


Using Ti-6Al-4V-1B alloy improves creep properties significantly




*Barboza, Neto, Silva "Creep mechanism and physical modeling for Ti-6Al-4V"
Material Science and Engineering A369 (2004)
201-209*




Backup slides



-5% Rigidity U beam profile on the BD shell (worst case)





SN curves for various Ti alloys



Backup slides


- Flow velocity profile verified in flow test with polystyrene beads ($\rho = 1.05 \text{ g/cm}^3$)



Backup slides

Chosen concept

- Water-filled rotating drum
 - » Most deposition occurs in water, minimize radiation damage to drum
 - » Adequate cooling accomplished with water through convection
 - » Flexibility in material selection to accommodate different requirements



Issues with other options

- Graphite disk beam dump
 - » excessive sublimation rates
 - » Insufficient cooling of disk where maximum power deposition occurs (Bragg peak)
 - » Buildup of inventories
 - » Minimal flexibility in material selection
- Liquid tin jet
 - » Significant instability of jet when rapidly heated
 - » Vaporization -> plating in beam line
 - » Size/complexity of molten metal loop required
 - » Few alternate materials for liquid metal jet

