
Neutrino Factory Mercury Flow Loop

V. Graves C. Caldwell

IDS-NF Videoconference March 9, 2010





Flow Loop Review


- 1 cm dia nozzle, 20 m/s jet requires 1.57 liter/sec mercury flow (94.2 liter/min, 24.9 gpm).
- MERIT experiment showed that a pump discharge pressure of ~40 bar gauge required to produce the desired jet.
 - Reference: SNS nominal flow 1440 liter/min (380 gpm), 7 bar gauge pump discharge pressure, ~1400 liters total Hg inventory
- Basic flow scheme

 $\textbf{Pump} \rightarrow \textbf{Nozzle} \rightarrow \textbf{Jet/Beam Dump} \rightarrow \textbf{Heat Exchanger} \rightarrow \textbf{Pump}$



Hg Flow


- Minimize pressure drops through piping by increasing diameter
 - 2" nozzle supply piping transitioning to 1 cm nozzle
- Actual NF Hg inventory may reach SNS volumes
 - ~500 liters in the halflength beam dump shown





Gravity Drain Requires Flow Control

- Bulk flow exits dump via overflow drains
- Gravity drain intended to remain closed until end-of run, but this liquid becomes static
- Decay heating requires gravity drain to have flow control





4 Managed by UT-Battelle for the U.S. Department of Energy

IDS-NF Videoconference, 9 Mar 2010

Target Building

- Based on Study 2 concept
- Mercury loop "hot cell" will probably extend into magnet chase
 - Could require double containment of mercury
 - Chase will certainly have a drain back into hot cell





Heat Removal

Element/Compound	Density (g/cm^3)
Hg	13.5
W	19.3
WC	15.8

- From Study 2, the mercury jet/pool receive < 10% of beam energy; bulk goes into WC shielding
 - Currently assumed to be WC spheres cooled by water
 - Much larger heat exchanger needed to cool shielding
- Considering that both W and WC must be water-cooled, their effective densities will approach that of Hg.
- Consequently, IF a Hg target is selected, the infrastructure will be in place to support use of Hg as a solenoid shield.
 - Would probably be a separate loop due to vastly different flow/pressure requirements, but could share a storage tank



Future Work

- Continue development of Target Building infrastructure conceptual design
- Look further into the mechanics of the region upstream of the nozzle
 - Remote maintenance / assembly / disassembly
 - Mercury flow

