

**Analytic Stress Calculations
for a Stepped Front Endplate**

K.T. McDonald

Princeton U.

May 9, 1996

Method

Use equations from Table 24, Case 2 of Roark and Young.

Evaluate the F_i and G_i functions separately on the two different steps.

Require continuity of deflection, slope, bending moment and shear force at the step.

Enforce conditions that $y_{\text{outer}} = y_{\text{inner}}$ and $M_{r,\text{outer}} = 0$ for a simple support there to determine $\text{slope}_{\text{inner}}$, $M_{r,\text{inner}}$ and $\text{shear}_{\text{inner}}$.

Then all values are readily determined as a function of radius.

Verify equations by using same thickness on both steps,
 \Rightarrow detailed agreement with Roark's examples.

Model Assumptions

The model is of a plate with no holes.

Use modulus for Al of $7/1.6 \times 10^{10}$ Pa, reducing by 1.6 for holes.

Multiply stresses by 2.5 to account for the stress concentration around holes (Roark, Table 37, Cases 6c & 7b).

Inner radius = 0.236 m.

Outer radius = 0.809 m.

Plate Simply Supported at Both Inner and Outer Radii

$r(\text{step})$ (cm)	Thick Thickness (mm)	Thin Thickness (mm)	Peak Deflection (mm)	Peak Radial Stress (MPa)
—	12	12	3.52	71.9
47	24	12	2.04	53.8
47	24	11	2.44	59.5
47	24	10	2.94	65.6
63	24	13	0.77	47.1
63	24	12	0.87	54.6
63	24	11	1.04	63.9
63	24	10	1.29	75.4

**Plate Fixed at Inner Radius,
Simply Supported at Outer Radius**

				Thick	Thin
$r(\text{step})$	Thick	Thin	Peak	Peak	Peak
(cm)	Thickness	Thickness	Deflection	Radial	Radial
	(mm)	(mm)	(mm)	Stress	Stress
				(MPa)	(MPa)
–	12	12	1.83	122.3	46.5
47	24	12	0.80	54.8	27.8
47	24	11	0.91	58.1	30.6
47	24	10	1.03	61.4	34.2
63	24	12	0.52	41.9	35.6
63	24	11	0.62	44.3	40.5
63	24	10	0.74	47.8	45.4

Remarks

1. We could reduce the peak stress by about 25% by using a step.
2. There is only a slight difference in the peak stress for a step at 47 cm compared to one at 63 cm.
3. The peak deflection is less for a step at 63 cm than one at 46 cm. This effect is more pronounced for simple supports at both inner and outer radii.
4. For a step at 47 cm there is no overall stress reduction in fixing the slope at the inner radius, as compared to a simple support there.
5. For a step at 63 cm there is a 25% stress reduction in fixing the slope at the inner radius, as compared to a simple support there.
6. For a step at 63 cm down to 13 mm a simply supported plate gives very similar performance to a step down to 10 mm for a plate fixed at the inner radius.
7. A step at 63 cm and a fixed slope at the inner radius offers

the greatest advantage in stress reduction and in minimizing deflection.

8. If we choose a step at 47 cm, an inner stiffening ring would be justified on the basis of the reduced deflection, not reduced stress.